

AUTOTROL 363 VALVE

AUTOMATIC FILTER VALVE

COMPACT, LOW-PROFILE SOLUTION FOR A BROAD RANGE OF FILTRATION APPLICATIONS



FEATURES / BENEFITS

• Compact, low-profile design for easy installation in tight spaces.

• 3" NPT inlet and outlet ports for easy connection to existing piping.

• 21" overall height, making it ideal for applications with limited vertical clearance.

• 1" NPT bleed-off port for easy maintenance and flushing.

• 3" NPT drain port for easy removal of debris and sediment.

• Built with durable, corrosion-resistant materials for long service life.

• Simple, intuitive operation with a single control valve.

• Compatible with a wide range of filter media and backwash systems.

• Available in multiple configurations to meet specific application needs.

OPTIONAL

• 604-1" NPT inlet and outlet ports for larger flow applications.

• 5"-1.25" NPT bleed-off port for enhanced maintenance capabilities.

• 3" NPT drain port for easy removal of debris and sediment.

• 604-1" NPT inlet and outlet ports for larger flow applications.



44



[illegible]

	120/230, ♯A
	120, ♯A
	100, ♯A
	240, ♯A
	240, ♯A
	240, ♯A
	240, ♯A

a

a

- a

a

A

P

P

4-20₁ l
21₁ l
5₁ l

2.5

1

4

0.5

Parameter	Value
β_1	3.35
β_2	1.05
β_3	-1.0 ± 0.5



5 30 5320
2 2.23 .4400 2 2.23 .4404 00.2 .404

All Pentair trademarks and logos are owned by Pentair, Inc. or its affiliates. All other registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

4002833 REV B MR14 © 2014 Pentair Residential Filtration, LLC All Rights Reserved.